

Technical data

Casing	: 19" / 3HE, 310mm deep
Exterior dimensions	: ca. 399mm x 133mm x 310mm
Weight	: Basic equipment : 5,6 kg (with 1x Output stage board for 3 axes) max. : 6,9 kg (with 6x Output stage board for 18 axes)
Input voltage	: 85V – 265V AC, 47 – 63 Hz
Performance	: max. 250W
Power Factor	: Meets EN61000-3-2 (Typical PF 0,98/0,95)
Current	: max. 2,5A bei 115VAC / 1,4A bei 230VAC
Inrush current	: 20A/40A (115V/230VAC)
Fuse	: 2 x T2,5A
Ambient temperature	: 0°C – 40°C
Relative humidity	: max. 90%
Number of Output stage	: 3 to 18

Technical data

Low Voltage Directive:

2006/95/EG Directive of European Parliament and of the Council of 12. December 2006
(until **19.04.2016**)

2014/35/EU Directive of European Parliament and of the Council of 26. February 2014
Official Journal of the EU L96, 29/03/2014, p. 357 – 374 (**from 20.04.2016**)

EMC-Directive:

2004/108/EG Directive of European Parliament and of the Council of 15. December 2004
(until **19.04.2016**)

2014/35/EU Directive of European Parliament and of the Council of 26. February 2014
Official Journal of the EU L96, 29/03/2014, p. 79 – 106 (**from 20.04.2016**)

EN 61010-1:2010 + Cor.:2011

Related to directive

Safety requirements for electrical equipment for measurement, control and
laboratory use - Part 1: General requirements

EN 61326-1:2013

Related to directive

Electrical equipment for measurement, control and laboratory use- EMC
requirement - Part 1: General requirements