PC-100

Versatile and easy-to-use puller by automated double pulling

PC-100 enables the user to produce many kinds of pipettes including pipettes with a tip of a few micrometers to be used for the experiments in biotechnology, those with a tip of a few micrometers to be used for the experiments in electrophysiology, and even those with a tip in the region of 1µm. In terms of producing pipettes with a wide variety of shapes and tips, the function of Mode selector button allows to choose a pulling mode setting between one-stage and two-stage. Once the value has been determined, the specification of PC-100 allows the user to reproduce the same pipette as the last one. In addition, the PC-100 applies free fall by gravity as its pulling force (or descending by the action of a weight), thus it is provided with two types of weights; a light type and a heavy type, two pieces each that is attach/detachable respectively in order to adjust the pulling force. The PC-100 enables you to pull various kinds of pipettes by all those settings of output voltage, pulling mode between one-stage and two-stage, and pulling force adjusted by weights.



* The PC-100 is designed specifically for pulling ø1mm~1.5mm O.D. borosilicate glass capillaries. For pulling capillaries of different O.D. or different materials, contact us or your local Narishige representative.

Features (changes from PC-10)

PC-100 is a compatible model with PC-10. The basic function remains the same. Operability is greatly improved.

- Simple and easy to use; set-up is easier than ever.
- Digital display clearly shows status and setting.
- Heating value can be adjusted as needs, even after the needle is placed in the heater coil.
- Acrylic cover closes securely.
- Elapsed time (from the "START" to end.) shows on display.
- The slider unit is protected from dust and debris.

Specification

Accessories included	Glass Capillary with Filament (ø1mm × 90mm) Spare Heater (Kanthal wire) AC Power cord
Working voltage	AC100V ~ AC240V, 50/60Hz
Power consumption	Approx. 70W
Heating element	Kanthal wire heater / 2.5V at maximum
Weight	Approx. 25g × 2 Approx. 100g × 2
Dimensions/Weight	W205 × D190 × H185mm, 3.45kg