



*Inverted trinocular LED fluorescence microscope, IOS U-PLAN F objectives, 6MP camera with 12" monitor*

<b>Observation Method - Transmitted Light</b>	Brightfield	Yes
	Phase contrast (Positive type)	As optional
<b>Observation Method - Incident Light</b>	Fluorescence	Yes
<b>Main Body</b>	Type	Inverted
	Construction material	Aluminum die-cast
<b>Head</b>	Type	Trinocular (Siedentopf)
	Split ratio	100/0 - 50/50
	Inclination	45°
	Interpupillary distance (mm)	50-75
	Diopter adjustment	On left tube
	Tube inner diameter (mm)	30
<b>Eyepieces</b>	Field number (mm)	22
	Magnification	10x
	Planar type	Yes
	Micrometric scale	As optional
	Diameter of micrometer glass (mm)	26
	High eyepoint (for glass wearers)	Yes
	Rubber cup	Yes
	Retractable protections	Yes
<b>Nosepiece</b>	Positions	Quintuple
	Reversed	Yes
	Bi-directional	Yes
	Rotation on ball bearings	Yes
	Objective thread	RMS
<b>Objectives</b>	Optical system	$\infty$
	Anti-fungus treatment	Yes
	Parfocal distance (mm)	45
	Standard magnifications	100x-400x
	Type	IOS LWD U-PLAN F

	IOS LWD U-PLAN F 10x/0.30, W.D. 7.11 mm
	IOS LWD U-PLAN F 20x/0.45, W.D. 5.91 mm
	IOS LWD U-PLAN F 40x/0.65, W.D. 1.61 mm

<b>Stage</b>	Type	Fixed + Attachable mechanical stage
	Dimensions (mm)	250x160 (fixed stage) 250x290 (with mechanical stage mounted)
	Moving mechanism	Rack and pinion
	Moving range (mm)	120x80
	Material	Anti-scratch painting
	Glass round insert	Yes
	Metal round insert	Yes
	Holder for Petri dish (mm)	54 (Included), 38, 65 (As optional)
	Holder for Terasaki plate	96 well
	Holder for 1 slide	Yes
	Holder for 2 slides	As optional
	Holder for Utermöhl chamber	As optional

<b>Condenser - Single Position</b>	Type	Abbe
	Removable	Yes
	Numerical aperture (N.A.)	0.30
	Diaphragm	Iris
	Long working distance	Yes
	Working distance (for LWD) (mm)	72
	Extendable working distance (for LWD) (mm)	up to 150

<b>Focusing System</b>	Type	Coaxial coarse & fine
	Fine total travel (per single rotation) (mm)	0,2
	Fine graduations	100
	Fine resolution (µm)	2
	Upper stop to prevent contact	Yes
	Adjustable tension	Yes

<b>Transmitted Illumination</b>	Type	X-LED
	X-LED type	X-LED8
	Light source power (W)	8
	Brightness control	Manual
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
	Max. required power (W)	13

<b>Power Supply for Transmitted Illumination</b>	Type	External
	Microscope connector	Jack, 2.1 mm
	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	12 Vdc 10 A

<b>Accessories Included</b>	Dust cover	Yes
	Allen wrench	Yes
	User Manual	Digital version (downloadable)

<b>Additional Information</b>		Metallic interchangeable inserts for slides, Petri dishes, Terasaki, multi-Well plates (as optional).
<b>Product Dimensions</b>	Height (mm)	495
	Width (mm)	365
	Depth (mm)	540
<b>Product Weight</b>	(kg)	12
<b>Fluorescence Attachment</b>	Number of LED Cubes	Up to 4
	<b>BLUE</b> LED Cube (Optional)	LED Emission: 460 nm. Excitation: 455 - 495 nm; Dichroic: 500 nm; Emission: 510LP nm
	<b>BLUE BANDPASS</b> LED Cube (Optional)	LED Emission: 460 nm. Excitation: 455 - 495 nm; Dichroic: 500 nm; Emission: 518-542 nm
	<b>GREEN</b> LED Cube (Optional)	LED Emission: 523 nm. Excitation: 510 - 550 nm; Dichroic: 570 nm; Emission: 575LP nm
	<b>GREEN BANDPASS</b> LED Cube (Optional)	LED Emission: 523 nm. Excitation: 510 - 550 nm; Dichroic: 570 nm; Emission: 585-625 nm
	<b>UV</b> LED Cube (Optional)	LED Emission: 365 nm. Excitation: 325 - 375 nm; Dichroic: 415 nm; Emission: 435LP nm
	<b>UV BANDPASS</b> LED Cube (Optional)	LED Emission: 365 nm. Excitation: 340 - 390 nm; Dichroic: 405 nm; Emission: 420-470 nm
	<b>V</b> LED Cube (Optional)	LED Emission: 405 nm. Excitation: 390 - 420 nm; Dichroic: 440 nm; Emission: 450LP nm
	<b>RED1</b> LED Cube (Optional)	LED Emission: 623 nm. Excitation: 590 - 650 nm; Dichroic: 660 nm; Emission: 665LP nm
	<b>RED2</b> LED Cube (Optional)	LED Emission: 623 nm. Excitation: 595 - 645 nm; Dichroic: 655 nm; Emission: 665-715 nm
	<b>DEEP RED</b> LED Cube (Optional)	LED Emission: 660 nm. Excitation: 623 - 678 nm; Dichroic: 685 nm; Emission: 690-750 nm
<b>FAR RED</b> LED Cube (Optional)	LED Emission: 740 nm. Excitation: 720 - 760 nm; Dichroic: 770 nm; Emission: 780LP nm	

	<b>AMBER LED Cube (Optional)</b>	LED Emission: 590 nm. Excitation: 582 - 603 nm; Dichroic: 610 nm; Emission: 615-645 nm
	Filter set selection	Manual
	LED source insertion	Manual
<b>Fluorescence Light Source</b>	Light source	LED Fluorescence Cube
	Light source power (W)	3,5
	LED wavelength	<i>see LED Fluorescence Cube specs</i>
	Lifetime (hours)	> 65,000
	Brightness control	Yes
<b>Camera General specifications</b>	USB output	Yes
	C-Mount	Yes
	Dimensions (mm)	68 x 68 x 46
	Weight (kg)	0.265
<b>Sensor</b>	Camera resolution (n° of pixels: W x H)	3072x2048
	Color / Monochrome	Color
	Sensor Size	1/1.8"
	Sensor Technology	CMOS
	Sensor Type	SONY EXMOR
	Image Format	3/2
	Pixel Size (mm)	2.4x2.4
	Acquisition technology	Rolling shutter
	Signal/Noise Ratio (DB)	41.74
	Dynamic range (DB)	66.8
	G sensitivity	425mV at 1/30s
	Dark Signal	0.15mV at 1/30s
	ADC conversion	8 Bit - 12Bit
	Color Depth	1, 4, 8, 24 Bit
	Exposure time	0.1 msec - 15 sec
	Binning	1x1; 2x2
IR filter	Yes	
IR filter range (nm)	380-650 (IR CUT)	
<b>USB</b>	Camera resolution (MP)	6.3
	USB standard	USB3.0
	Frame rate full resolution (fps)	30@3072x2048
	Frame rate other resolution (fps)	38@1536x1024
<b>Camera Power Supply</b>	Connector	USB
	Output voltage	PC USB
<b>Camera accessories</b>	Calibration slide	Yes
	USB cable (1.8m)	Yes
<b>Environment</b>	Working Temperature	-10°C up to +50°C
	Storage Temperature	-20°C up to +60°C
	Relative Humidity	30% to 80%
	Storage Humidity	10% to 60%
<b>Operating System</b>	OS	Windows 10 (64Bit)

<b>Available Software</b>	PC SW	PROVIEW
<b>PC requirements</b>	PC	CPU: Intel Core2 - 2.8GHz or higher
	PC	RAM: 2GB or more
	PC	USB 3.0
<b>HDMI Monitor</b>	Display size	12"
	Display resolution	1920x1080
	Contrast ratio	1000:1
	Power plug type	Built-in
	Input voltage	100/240 Vac, 50/60 Hz
	Input ports	HDMI
	Dimensions (mm)	300x190x20
	Weight (Kg)	0.6
<b>PC STICK</b>	Operating system	Windows 10 (64Bit)
	CPU	Intel Celeron N4000
	CPU speed	1.1GHz
	Graphic card	Included in CPU
	RAM	8GB
	Power plug type	Jack
	Input voltage	5V dc
	Storage	128GB
	WiFi	802.11 a/b/g/n/ac
	Input ports	USB
	Output ports	HDMI