



VIBRATION-FREE COUPLING VIA LIQUID LIGHT GUIDE

DIMMING VIA PWM OR CURRENT CONTROL

LIFETIME >50,000 HOURS

LONG STABLE LAMP LIFE

TTL AND ANALOG CONTROLS

INTEGRAL SHUTTERING

WHITE LIGHT AND UV COMBINATION AVAILABLE



LAMBDA HPX-L5 HIGH-OUTPUT LED LIGHT SOURCE

The **Lambda HPX-L5** was created as a liquid light guide coupled version of the HPX, our newest high power LED light source. The liquid light guide allows for LED cooling via an internal heatsink with a whisper fan. This requires less maintenance than the liquid-cooled direct mount version. Designed around a single 90W 3mm LED die, the **Lambda HPX-L5** provides light output comparable to a 150W xenon arc lamp when using the same light guide. The **Lambda HPX-L5** is optimized for coupling to an optional 5mm liquid light guide, and off-the-shelf microscope adapter. The **Lambda HPX-L5** is expected to retain 95% of its original output at 5000 hours, and 80% after 10,000 hours.

Because LEDs exhibit color shift with current change, the **Lambda HPX-L5** was designed to dim the LED using either PWM or current control. PWM will be preferable for most applications, and allows the LED to run cooler. PWM switching is at 28KHz, high enough for use with most high speed cameras.

For those with applications intolerant of any pulsed output, dimming via current control is also available. PWM and Current information are conveniently displayed on the front panel display, and are manually selectable via control knobs. Integral shuttering time is 10 microseconds to turn on and off. TTL input and output allows for triggering from either software or directly from another device such as a camera or digital IO board. PWM can also be controlled externally via analog input. Active temperature monitoring insures that the LED life will be maximized.

Light output is in the visible spectrum from 430nm - 700nm. Special order units are available with 630nm, 530nm, 460nm, and 405nm wavelength specific LEDs. The **Lambda HPX-L5** can also be combined with our **FLED** to create a two-channel system with any combination of wavelengths.

LAMBDA HPX-L5 SYSTEM

HPX-L5¹ – Lambda HPX-L5 LED Light Source

Available Wavelengths

WC-HPX-L5 LED, Cool White

460-HPX-L5 LED, 460nm

530-HPX-L5 LED, 530nm

630-HPX-L5 LED, 630nm

LAMBDA HPX-L5UV SYSTEM

HPX-L5UV¹ – Lambda HPX-L5UV LED Light Source

Available Wavelengths

405-HPX-L5 LED, 405nm

LAMBDA HPX-L5DC* – Includes the Lambda HPX-L5 LED light source with cool white LED, Lambda FLED with UV LED, and cables.

HPX-L5DC-Y¹ Lambda HPX and FLED for Olympus

HPX-L5DC-N¹ Lambda HPX and FLED for Nikon

HPX-L5DC-Z¹ Lambda HPX and FLED for Zeiss

HPX-L5DC-L¹ Lambda HPX and FLED for Leica

* Suitable for additional DAPI channel

¹ You will need a mounting adapter for your microscope



SUTTER INSTRUMENT

One Digital Drive • Novato • CA 94949 • Phone 415.883.0128
Fax 415.883.0572 • Web www.sutter.com • Email info@sutter.com

